

# Flat Rooflight Datasheet



- **Exceptional thermal performance**
    - ✓ Overall U value (double glazing and frame) 1.3 w/m<sup>2</sup>k
    - ✓ Structural PVCu internal core with superior thermal properties
  - **Minimal external and internal sightlines**
  - **Simple installation**
    - ✓ Hidden direct fixing and strap fixing alternative
    - ✓ Internal plasterboard pocket for easy boarding and plastering
    - ✓ Clip in external weather bar and internal cover trim
  - **Weather resistant** - 5 degree pitched kerb allowing the water to drain off the glazing unit unto the existing flat roof
  - **Insulated kerb upstands** available to purchase from Atlas
  - Standard toughened double glazed spec - 6mm active neutral solar/16mm gas/6mm Low e (U value 1.0 w/m<sup>2</sup>k)/self cleaning
  - **Manufactured** and **kitemarked** to BS EN 1279-2 and toughened to BS EN 12150-1
  - **10 year seal and easy clean coating warranty** as standard
  - Available (as standard) in:
    - Grey Ral 7016 matt
    - Black Ral 9005 matt
    - White Ral 9910 satin
    - Grey on white
    - Black on white
- | Stock sizes (internal measurements): |
|--------------------------------------|
| - 1000 x 1000 - 40kg                 |
| - 1000 x 1500 - 57kg                 |
| - 1000 x 2000 - 75kg                 |