

LANTERN DATA SHEET

System	
System	Full aluminium (thermally broken with polyamide break)
Spec	
Rafter depths	P401 rafter – 70mm
·	P402 rafter – 83mm
	P403 rafter – 100mm
Rafter width	40mm
Ridge width	40mm
Roof pitch	17 degrees to 35 degrees
External caps	Flat or moulded (aluminium or PVCu)
Boss & hoods	Not required
Tie bars (dependent on	Up to 2500mm wide - no tie bar
design)	Up to 3800mm wide - hidden
	Up to 5000mm - box
Rafter U Value	Double glazed - 1.5 W/m ² k
	Triple glazed - 0.95 W/m²k
Sill	No sill required (unless preferable)
	Options available - 150mm & 180mm PVCu
	- 150mm & 190mm aluminium
Upstand	Check with local building control authority
	67mm minimum width
Glazing	
Glass U Value	Double glazing - 1.1 W/m²k (0.9 W/m²k available on request)
Glass O value	Triple glazing - 0.6 W/m²k
Glass options	24mm 4mm neutral / blue active / 16mm argon / 4mm low e
(toughened outer and inner)	44mm 4mm riedital / bide active / 16mm argon / 4mm low e 44mm 4mm clear / 16mm argon / 4mm low e / 16mm argon / 4mm low e
	Self Clean (clear)
	Solar control self clean (blue, neutral) available in 24mm or 44mm units
Options	
Gutters	Available Aluminium or PVCu
Roof vents	Available on double glazing only
Roof vent options	Manual (with opening pole) or electric (with switch)
·	Rain/temperature sensor available
	Standard - aluminium exterior, PVCu interior (requires glazing at top)
	Premium - fully aluminium (positioned under the ridge)
Colours	Stock - white / grey / grey on white / black / black on white
	Bespoke- any RAL colour and dual combinations available
Delivery	
Delivery lead times	Bespoke white - 2 to 3 weeks
(from confirmation of	Bespoke grey or black - 3 to 4 weeks
drawings)	All stock - 3 to 4 weeks
	Any other - from 6 weeks
Packaging	All roof parts – cut to size and numbered
Approx fitting time	Half day
(dependent on size)	



LANTERN KERB DETAIL

